ABB ABB Series Service Manual

AO801

1. Description

The AO801 Analog Output Module has 8 unipolar analog output channels. The module performs selfdiagnostic cyclically. A low internal power supply sets the module in INIT state (no signal from the module).

3. Product Information

The AO801 Analog Output Module has 8 unipolar analog output channels. The module performs selfdiagnostic cyclically. A low internal power supply sets the module in INIT state (no signal from the module).

Features and benefits

8 channels of 0...20 mA, 4...20 mA outputs

OSP sets outputs to predetermined state upon error detection

Analog Output is to be short circuit secured to ZP or +24 V

Process and power connection via detachable connectors

General info

Article number 3BSE020514R1

Type Analog Output

Signal specification 0... 20 mA, 4...20 mA

Number of channels 8

Signal type Unipolar single ended

HART No

SOE No

Redundancy No

High integrity No

Intrinsic safety No

Mechanics S800L

Detailed data

Resolution 12 bit

Isolation Groupwise isolated from ground

Under/over range - / +15%

Output load Max 850 Ω

Error 0,1 %

Temperature drift Typ 30 ppm/°C, Max 50 ppm/°C

Rise Time 10 µs

Update cycle time 1 ms

Current limiting Short circuit proof current limited output

Maximum field cable length 600 meters (656 yards)

Rated insulation voltage 50 V

Dielectric test voltage 500 V a.c.

Power dissipation 3.8 W

Current consumption +5 V Modulebus 70 mA

Current consumption +24 V Modulebus -

Current consumption +24 V external 200 mA

Supported wire size Solid: 0.05-2.5 mm², 30-12 AWG

Stranded: 0.05-1.5 mm², 30-12 AWG

Recommended torque: 0.5-0.6 Nm

Stripping length 6-7.5mm, 0.24-0.30 inch

Diagnostics

Front LED’s S(tatus) (run or fault)

Status indication of supervision Module Error, Module Warning, Channel error

Environment and certification

CE mark Yes

Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201

Hazardous Location C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2

Marine certification ABS, BV, DNV, LR

Temperature, Operating 0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C

Temperature, Storage -40 to +70 °C (-40 to +158 °F)

Pollution degree Degree 2, IEC 60664-1

Corrosion protection ISA-S71.04: G3

Relative humidity 5 to 95 %, non-condensing

Max ambient temperature 55 °C (131 °F), for vertical mounting 40 °C (104 °F)

Protection class IP20 according to IEC 60529

Mechanical operating conditions IEC/EN 61131-2

EMC EN 61000-6-4 and EN 61000-6-2

Overvoltage categories IEC/EN 60664-1, EN 50178

Equipment class Class I according to IEC 61140; (earth protected)

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Dimensions

Width 86.1 mm (3.4”)

Depth 58.5 mm (2.3”)

Height 110 mm (4.33”)

Weight 0.24 kg (0.53 lbs.)