ABB ABB Series Service Manual

DI818

1. Description

This module has 32 digital inputs. The input voltage range is 18 to 30 volt d.c. and the input current is 4.3mA at 24 V. The inputs are divided into two individually isolated groups with 16 channels and one voltage supervision input in each group. Every input channel consists of current limiting components, EMC protection components, input state indication LED and optical isolation barrier. The process voltage supervision input give channel error signals if the voltage disappears. The error sign

3. Product Information

This module has 32 digital inputs. The input voltage range is 18 to 30 volt d.c. and the input current is 4.3mA at 24 V. The inputs are divided into two individually isolated groups with 16 channels and one voltage supervision input in each group. Every input channel consists of current limiting components, EMC protection components, input state indication LED and optical isolation barrier. The process voltage supervision input give channel error signals if the voltage disappears. The error signal can be read via the ModuleBus.

Features and benefits

32 channels for 24 V d.c. inputs with current sinking

Two Isolated groups of 16 channels with voltage supervision

Voltage Supervision

Signal Filtering

MTUs that match this product

,

TU818

General info

Article number 3BSE069052R1

Type Digital Input

Signal specification 24 V d.c.

Number of channels 32

Signal type Current sinking

HART No

SOE No

Redundancy No

High integrity No

Intrinsic safety No

Mechanics S800

Detailed data

Input voltage range, "0" -30 .. +5 V

Input voltage range, "1" 11 .. 30 V

Input impedance 5.6 kΩ

Isolation Groupwise isolated from ground, groups of 16 channels

Filter times (digital, selectable) 2, 4, 8, 16 ms

Current limiting Sensor power can be current limited by the MTU

Maximum field cable length 600 meters (656 yards)

Rated insulation voltage 50 V

Dielectric test voltage 500 V a.c.

Power dissipation Typ. 3.1 W

Current consumption +5 V Modulebus 70 mA

Current consumption +24 V Modulebus 0

Current consumption +24 V external 25 mA

Diagnostics

Front LED’s F(ault), R(un), W(arning), Channel 1-16 ("0" or "1")

Supervision Process voltage, 1 per group

Status indication of supervision Module Error, Module Warning, Channel error

Environment and certification

CE mark Yes

Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201

Hazardous Location -

Marine certification ABS, BV, DNV, LR

Temperature, Operating 0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C

Temperature, Storage -40 to +70 °C (-40 to +158 °F)

Pollution degree Degree 2, IEC 60664-1

Corrosion protection ISA-S71.04: G3

Relative humidity 5 to 95 %, non-condensing

Max ambient temperature 55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)

Protection class IP20 according to IEC 60529

Mechanical operating conditions IEC/EN 61131-2

EMC EN 61000-6-4 and EN 61000-6-2

Overvoltage categories IEC/EN 60664-1, EN 50178

Equipment class Class I according to IEC 61140; (earth protected)

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Compatibility

Use with MTU TU818, TU819, TU830

Keying code EA

Dimensions

Width 45 mm (1.77”)

Depth 102 mm (4.01”), 111 mm (4.37”) including connector

Height 119 mm (4.7”)

Weight 0.15 kg (0.33 lbs.)