ABB ABB Series Service Manual

DI828

1. Description

The DI828 is an 16 channel 120 V a.c/d.c. digital input module for the S800 I/O. The module has 16 digital inputs. The AC input voltage range is 77 - 130 V and the input current is 8.5 mA at 120V AC. The DC input voltage range is 75 - 130 V and the input current is 2.4 mA at 120V DC. The inputs are individually isolated.

3. Product Information

The DI828 is an 16 channel 120 V a.c/d.c. digital input module for the S800 I/O. The module has 16 digital inputs. The AC input voltage range is 77 - 130 V and the input current is 8.5 mA at 120V AC. The DC input voltage range is 75 - 130 V and the input current is 2.4 mA at 120V DC. The inputs are individually isolated.

Every input channel consists of current limiting components, EMC protection components, input state indication LED, optical isolation barrier and an analog filter. Channel 1 can be used as voltage supervision input for channels 2 - 8. Channel 16 can be used as voltage supervision input for channels 9 - 15.

If the voltage supervision is used and the voltage connected to channel 1 or 16 disappears, the channel error will be set for the channels and the Warning LED turns on. The error signal can be read from the ModuleBus.

Features and benefits

16 channels for 120 V AC/DC inputs

Individually isolated channels

Input status indicators

Signal filtering

MTUs that match this product

,

TU851

General info

Article number 3BSE069054R1

Type Digital Input

Signal specification 120 V a.c. / d.c.

Number of channels 16

Signal type Current sinking

HART No

SOE No

Redundancy No

High integrity No

Intrinsic safety No

Mechanics S800

Detailed data

Input voltage range, "0" 0..30 V a.c., 0..20 V d.c.

Input voltage range, "1" 77..130 V a.c., 75..130 V d.c.

Input impedance 14.2 kΩ (a.c.) / 50 kΩ (d.c.)

Isolation Individually isolated channels

Filter times (digital, selectable) 2,5 ±0.5, 5 ±1, 10 ±2, 20 ±4 ms

Input frequencey range 47..63 Hz

Analog filter On/Off delay 5 / 10 ms

Maximum field cable length 200 meters (656 yards) 100 pF/m for a.c., 600 meters (656 yards) for d.c.

Rated insulation voltage 250 V

Dielectric test voltage 2000 V a.c.

Power dissipation Typ. 3.5 W

Current consumption +5 V Modulebus Typ. 45 mA, Max 60 mA

Current consumption +24 V Modulebus 0

Diagnostics

Front LED’s F(ault), R(un), W(arning), Channel 1-16 ("0" or "1")

Supervision Process voltage, Channel 1 and 16 can be used per group

Status indication of supervision Module Error, Module Warning, Channel error

Environment and certification

CE mark Yes

Electrical safety EN 61010-1, UL 61010-1, EN 61010-2-201, UL 61010-2-201

Hazardous Location -

Marine certification ABS, BV, DNV, LR

Temperature, Operating 0 to +55 °C (+32 to +131 °F), approvals are issued for +5 to +55 °C

Temperature, Storage -40 to +70 °C (-40 to +158 °F)

Pollution degree Degree 2, IEC 60664-1

Corrosion protection ISA-S71.04: G3

Relative humidity 5 to 95 %, non-condensing

Max ambient temperature 55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F)

Protection class IP20 according to IEC 60529

Mechanical operating conditions IEC/EN 61131-2

EMC EN 61000-6-4 and EN 61000-6-2

Overvoltage categories IEC/EN 60664-1, EN 50178

Equipment class Class I according to IEC 61140; (earth protected)

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Compatibility

Use with MTU EB

Keying code TU851

Dimensions

Width 45 mm (1.77”)

Depth 102 mm (4.01”), 111 mm (4.37”) including connector

Height 119 mm (4.7”)

Weight 0.15 kg (0.33 lbs.)