ABB ABB Series Service Manual

SD832

1. Description

The SD832 Power Supply Units are designed to meet all the applicable electrical safety data stated by the EN 50178 harmonized European Standard Publication and the additional safety and function data required by EN 61131-2 and UL 508.

3. Product Information

The SD832 Power Supply Units are designed to meet all the applicable electrical safety data stated by the EN 50178 harmonized European Standard Publication and the additional safety and function data required by EN 61131-2 and UL 508.

The secondary output circuitry is accepted for SELV or PELV applications. It is switch-mode Power Supply Units that converts the mains voltage to 24 volts d.c. These power supplies can be utilized for non-redundant and redundant applications.

Redundant applications require diode voting units SS823 or SS832. With the SD832 Power Supply Units, it is no requirement for the installation of a mains filter. It provides a soft start feature; power-on of an SD832 will not trip fuse or earth-fault circuit breaker.

Features and benefits

Simple DIN-rail mounting

Class I Equipment, (when connected to Protective Earth, (PE))

Over-voltage Category III for connection to primary main

TN network

Protective separation of secondary circuit from primary circuit

Accepted for SELV and PELV applications

The output of the units is protected against over current

(current limit) and over voltage (OVP)

General info

Article number 3BSC610065R1

Type Power supply

Rated output current 5 A

Rated output power 120 W

Rated output voltage d.c. 24 V

Rated input power 240/283 VA

Mains/input voltage, nominal 100-120 V a.c. 200-240 V a.c. Auto-select input

Applications SELV and PELV

Efficiency 89.4/90.2 %

Detailed data

Mains voltage variation allowed 100-120 V a.c. +-10 %, 200-240 V a.c. +-10 %

Mains frequency 50-60 Hz +-6 %

Primary peak inrush current at power on <10 A

Load sharing -

Supervision relay NO

Power Factor (at rated output power) 0.56/0.47

Heat dissipation 14/13 W

Output voltage regulation at max. current < 70 mV / <100 mV

Ripple (peak to peak) < 50 mV

Secondary voltage holdup time at mains blackout 80/78 ms

Maximum output current 6 A At ambient temp < 45 °C

Maximum ambient temperature 55 °C

Primary: Recommended external fuse 10-20 A

Secondary: Short circuit 10-14 A

Output over voltage protection < 39 V

Environment and certification

CE mark Yes

Electrical safety IEC 61131-2, UL 508, EN 50178

ATEX Zone 2 No

IECEx Zone 2 No

Hazardous Location, Class 1 Div 2 No

Marine certification ABS, BV, DNV-GL, LR

Protection rating IP20 according to IEC 60529

Corrosive atmosphere ISA-S71.04 G2

Pollution degree Degree 2, IEC 60664-1

Mechanical operating conditions IEC 61131-2

EMC EN 61000-6-4 and EN 61000-6-2

Overvoltage Categories Over-voltage Category III (IEC/EN 60664-1)

Equipment class Class 1 according to EN 50718; 3.56

RoHS compliance DIRECTIVE/2011/65/EU (EN 50581:2012)

WEEE compliance DIRECTIVE/2012/19/EU

Dimensions

Width 32 mm (1.26")

Depth 117 mm (4.61")

Height 124 mm (4.88")

Weight (lbs.) 500 g (1.1 lbs.)

Mounting spacing W mm 15 mm (0.59")

Mounting spacing H mm 40 mm (1.57")