Bently Nevada 21022 Series Service Manual

21022-29-10-017-03

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. :21022-29-10-017-03

Product Type : Dual Axial Probe Housing Assembly

Made in U.S.A

Probe Option, with Connector: 29 = 3300 XL 11 mm probe

Probe Cable Length Option 10 = 1.0 metre (39 in)

3300 XL 11 mm Probe not available with 0.5 meter Probe Cable Length.

Probe Penetration Option 017= 1.7 in

Fittings Option 03= Two cable seal grips with grommets for cable sizes 1/8-in to 3/16-in, 1/4-in to 5/16-in, 5/16-in to 3/8-in; two 3/4-14 to 1/2-14 NPT reducers

Fittings option are supplied as a kit and are not installed when the housing is shipped.

The 21022 Dual Axial Probe Housing Assembly consists of two
proximity probes installed in an externally mounted
protective enclosure. It is intended for mounting on the end of
a machine nearest the thrust bearing to allow both probes to
observe the end of the shaft for axial thrust position
movement. The enclosure mounts on the machine case
using four standard machine screws. The probes are
mounted in sleeve/adapter assemblies, which are installed
directly onto the machine case through two 3/4-in NPT
threaded holes.

The dual axial position housing meets the American
Petroleum Institute’s (API) 670 Standard for axial thrust
position transducer housings. The external mounting allows
probe adjustments from outside the machine, while
protecting the proximity probes, probe leads, and extension
cables from dust, splashing liquid, or other environmental
factors. A removable cover on the enclosure provides access
for setting the probe gaps.

21022

Aluminum alloy housing (sand cast,
0.3% copper free) with sleeves fabricated
from 304 stainless steel

3.6 kg (8 lb)