Bently Nevada 31000&32000 Series Service Manual

31000-16-05-00-023-02-02

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. :31000-16-05-00-023-02-02

Product type : 31000 Proximity Probe Housings

Made in U.S.A

Probe Option, With Connector : 16 = 3300 XL 8 mm probe

Probe Cable Length Option : 05 = 0.5 m (20 in)

Standoff Adapter Option : 00=No standoff adapter

Probe Penetration Option : 023=2.3 in

Fittings Option :02 = Two 3/4-14 NPT fittings, one plug.

Mounting Thread Option : 02 = 3/4-14 NPT (Required if ordering Standoff Adapter Option)

Protection Ratings: Type 4X rating certified by Canadian Standards Association (CSA). IP66 rating verified by SC115582-1 (e) 106. CENELEC standard EN50014 rating for electrostatic dissipation of a plastic material located in a hazardous area.

Housing Material: Glass-reinforced Polyphenylene Sulfide (PPS) thermoplastic containing conductive fibers

Sleeve Material and Retaining Chain: AISI 304 stainless steel

Outer Sleeve and Exterior Screws: AISI 303 stainless steel

O-Ring Material: Neoprene®

Housing Impact Strength: Certified by BASEEFA to withstand two separate 4 Joule (3.0 ft·lb) impacts at -39°C (-38°F) and at 115 °C (239°F). Samples of the housing and cover were verified by CSA to withstand a 7 Joule (5.2 ft·lb) impact at ambient room temperature.

Temperature Rating: -51°C to +105°C (-60°F to +221°F)

Weight : 1.2 Kg

Probe Pressure

The 31000/32000 Proximity Probe Housing
Assembly is designed to seal differential
pressure between the probe tip and the
housing main body when used with a 3300 XL 8
mm probe. The sealing material internal to the
probe case consists of a Viton O-ring; the Oring between the sleeve and the housing is a
Neoprene O-ring. The plastic housing is certified to seal against hose-directed water
according to NEMA 4X and IP66 standards but
is not designed to resist internal or external
pressure. Probes are not pressure tested prior
to shipment. Contact our custom design
department if you require a test of the pressure
seal for your application.

Protection
Ratings
Type 4X rating certified by
Canadian Standards Association
(CSA). IP66 rating verified by
SC115582-1 (e) 106. CENELEC
standard EN50014 rating for
electrostatic dissipation of a plastic
material located in a hazardous
area.

Housing
Material
Glass-reinforced Polyphenylene
Sulfide (PPS) thermoplastic
containing conductive fibers

Sleeve Material
and Retaining
Chain
AISI 304 stainless steel

Outer Sleeve
and Exterior
Screws
AISI 303 stainless steel

O-Ring
Material Neoprene

Recommended Torque (retaining nut)	29.4 N·m (260 in·lb)
Housing Strength (typical)	Outer sleeve was mounted on a test stand with its axis parallel to horizontal and the housing mounted on the outer sleeve through an end hole. The housing supported 912 N (205 lb) placed approximately 38 mm (1.5 inches) from the unsupported end with the cover fastened in place and grounding liner installed.
Housing Impact Strength	Certified by BASEEFA to withstand two separate 4 Joule (3.0 ft·lb) impacts at -39°C (-38°F) and at 115 °C (239°F). Samples of the housing and cover were verified by CSA to withstand a 7 Joule (5.2 ft·lb) impact at ambient room temperature.
Weight	1.2 kg (2.6 lb) typical