Bently Nevada 330105&330106 Series Service Manual

330106-05-30-15-12-00

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. 330106-05-30-15-12-00

Product Type : 3300 XL 8 mm Reverse Mount Probes

Made in U.S.A

330106-05-30-CC-DD-EE M10 x 1 threads

Total length option : 15 = 1.5 meter (4.9 feet)

Connector option :

12 = Miniature ClickLoc coaxial connector , FluidLoc cable

The FluidLoc cable option –12 is not
necessary on the vast majority of
330105 and 330106 installations due
to the presence of the probe sleeve.
Consider carefully the application
before ordering the FluidLoc cable
option for these probes.

Agency approval option :CN=Country Specific

Probe tip material : Polyphenylene sulfide (PPS).

Probe case material : AISI 303 or 304 stainless steel (SST).

Nominal Probe DC Resistance

Resistance (RPROBE) from Center Conductor
to Outer Conductor

Probe Length (m) 1.5

RPROBE(Ω) 7.73 ± 0.50

Mechanical

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material

AISI 303 or 304 stainless steel
(SST).

Probe Cable Specifications

Standard
cable

75Ω triaxial, fluoroethylene
propylene (FEP) insulated
probe cable in the following
total probe lengths: 0.5, 1, 1.5, 2,
3, 5, or 9 meters.

Extended
Temperature
Range cable

75Ω triaxial, perfluoroalkoxy
(PFA) insulated probe cable in
the following total probe
lengths: 0.5, 1, 1.5, 2, 5, or 9
meters.

Armor
(optional on
both)

Flexible AISI 302 or 304 SST
with FEP outer jacket.

Tensile
Strength
(Maximum
Rated)

330 N (75 lbf) probe case to
probe lead.
270 N (60 lbf) at probe lead to
extension cable connectors.

Connector

Material

Gold-plated brass or goldplated beryllium copper.

Probe Case Thread M10x1

Maximum Length of Thread Engagement 15 mm

Probe 323 g/m (11.4 oz)

Probe Temperature Range

Operating and Storage Temperature

Standard

Probe

-52°C to +177°C (-62°F to

+350°F)

Extended

Temperature

Range Probe

-52°C to +218°C (-62°F to

+425°F) for the probe tip; -

51°C to +260°C (-60°F to

+500°F) for the probe cable

and connector.

Exposing the probe to temperatures

below –34˚C (-30˚F) may cause

premature failure of the pressure

seal.

Probe Pressure

3300 XL 8 mm probes are designed to seal

differential pressure between the probe tip

and case. The probe sealing material consists

of a Viton® O ring. Probes are not pressure

tested prior to shipment. Contact our custom

design department if you require a test of the

pressure seal for your application.

Probe Relative Humidity

Less than a 3% change in Average Scale

Factor (ASF) when tested in 93% humidity in

accordance with IEC standard 68 2 3 for up to

56 days.