Bently Nevada 330703&330704&330705&330709&330 Series Service Manual

330703-000-060-10-02-00

1. Description

Part Number: 330703-000-060-10-02-00

3. Product Information

Part Number: 330703-000-060-10-02-00

Model: 3300 XL 11 mm Proximity Probes, Metric

Brand: Bently Nevada

Condition: New & Original in Factory Packing

Factory Warranty: 12 Months

Ordering Information

Model: 330703 - 3300 XL 11 mm Probe, M14 x 1.5 thread, without armor

Unthreaded Length Option: 000 - 00 mm

Overall Case Length Option: 060 - 60.0 mm

Total Length Option: 10 - 1.0 metres (3.3 feet)

Connector and Cable Type Option:

02 Miniature coaxial ClickLoc connector, standard cable

Agency Approval Option: 00 Not required

Probe dc Resistance

Probe

Length (m)

Resistance from the Center

Conductor to the Outer

Conductor (RPROBE) (ohms)

1.0 5.9 ± 0.5

Effects of 60 Hz Magnetic Fields Up to 300

Gauss (5 meter system)

Output voltage in mil pp/gauss

Gap Probe

0.5 mm (20 mil) 0.001

2.5 mm (100 mil) 0.009

4.6 mm (180 mil) 0.027

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material AISI 304 stainless steel (SST).

Probe Cable

Specification

75 Ω triaxial, fluoroethylene

propylene (FEP) insulated

probe cable in the following

total probe lengths: 1, 5 or 9

meters.

Probe Case Torque

Maximum 63.3 N•(560 in•lb)

Rated Recommended

21.1 N•m (187 in•lb)

Probe

Case

Thread

Maximum Length of Thread

Engagement

M14x1.5 21 mm

Probe Temperature Range

Operating and

Storage

Temperature

-52°C to +177°C (-62°F to

+351°F)

Exposing the probe to temperatures

below -34°C (30°F) may cause

premature failure of the pressure

seal.

Temperature Schedule

Temperature

Classification

Ambient Temperature

(Probe Only)

For EPL Ga and Gc

T1 -55°C to +232°C

T2 -55°C to +177°C

T3 -55°C to +120°C

T4 -55°C to +80°C

T5 -55°C to +40°C

For EPL Dc

T280°C @ Ta -55°C to +232°C

T225°C @ Ta -55°C to +177°C

T170°C @ Ta -55C to +120°C

T130°C @ Ta -55°C to +80°C

T105°C @ Ta -55°C to +100°C

T90°C @ Ta -55°C to +40°C