Bently Nevada 330703&330704&330705&330709&330 Series Service Manual

330709-000-060-50-11-00

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. : 330709-000-060-50-11-00

Product type : 3300 XL 11 mm Proximity Probes

Made in U.S.A

330709 =3300 XL 11 mm Probe, M16 x 1.5 thread, without armor

Unthreaded Length Option : 000 = 0 mm

Overall Case Length Option : 060 =60mm

Total Length Option : 50= 5.0 meters (16.4 feet)

Five meter probes are designed for use with the five meter Proximitor Sensor only.

Connector and Cable-Type Option : 11= Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

Agency Approval Option : 00= Not required

Probe dc Resistance

Probe

Length (m) 5.0

Resistance from the Center Conductor to the Outer Conductor (RPROBE) (ohms)

7.2 ± 0.8

Cross-talk Limitation:

Target Size - Flat Surface

Diameter

Recommended

Minimum 30.5 mm (1.2 in)

Shaft Diameter

Recommended

Minimum 152 mm (6.0 in)

Probe Tip

Material Polyphenylene sulfide (PPS).

Probe Case

Material AISI 304 stainless steel (SST).

Probe Cable

Specification

75 Ω triaxial, fluoroethylene propylene (FEP) insulated probe cable in the following total probe lengths: 1, 5 or 9 meters.

Connector-to-connector torque

Recommended torque Finger tight

Maximum torque 0.565 N•m (5 in•lb)

Minimum Bend Radius (with or without SST armor)

25.4 mm (1.0 in)

Probe Case Thread M16x1.5

Maximum Length of Thread Engagement 24 mm

Probe Temperature Range

Operating and Storage Temperature

-52°C to +177°C (-62°F to +351°F)

Exposing the probe to temperatures below -34°C (30°F) may cause premature failure of the pressure

seal.

Probe Case Thread M16x1.5

Maximum Length of Thread

Engagement 24 mm

Probe Case Torque

M14x1.5 and

M16x1.5 probe

cases

Maximum Rated 63.3 N•m (560 in•lb)

Recommended 21.1 N•m (187 in•lb)

Temperature Schedule

(Probe Only)

For EPL Ga and Gc

Temperature Classification T1; Ambient Temperature -55°C to +232°C

Temperature Classification T2 ;Ambient Temperature -55°C to +177°C

Temperature Classification T3; Ambient Temperature -55°C to +120°C

Temperature Classification T4; Ambient Temperature -55°C to +80°C

Temperature Classification T5; Ambient Temperature -55°C to +40°C

For EPL Dc

Temperature Classification T280°C @ Ta ;Ambient Temperature -55°C to +232°C

Temperature Classification T225°C @ Ta ;Ambient Temperature -55°C to +177°C

Temperature Classification T170°C @ Ta; Ambient Temperature -55C to +120°C

Temperature Classification T130°C @ Ta; Ambient Temperature -55°C to +80°C

Temperature Classification T105°C @ Ta; Ambient Temperature -55°C to +100°C

Temperature Classification T90°C @ Ta; Ambient Temperature -55°C to +40°C