Bently Nevada 330880&330881 Series Service Manual

330880-16-00-025-03-02

1. Description

Manufacturer : Bently Nevada

3. Product Information

Manufacturer : Bently Nevada

Product No. : 330880-16-00-025-03-02

Product Type : PROXPAC XL Proximity Transducer

Made in U.S.A

Probe and Approvals Option :1 6= 3300 XL 8 mm probe without approvals

Standoff Adapter Option (B Dimension) : 0 0 =No standoff adapter

Probe Penetration Option (C Dimension) : 025= 25mm

Fittings Option : 0 3:

One 3/4-14 NPT fitting, one 3/4-14 NPT

to 1/2-14 NPT SST reducer and two

plugs

Mounting Thread Option :0 2:

3/4-14 NPT (Required if ordering

Standoff Adapter Option.)

Weight : 1.44 Kg

Mechanical

Housing Ratings

IP66 rating verified by BASEEFA

report number T07/0709.

Probe Tip

Material

Polyphenylene Sulfide (PPS)

Probe Case

Material

AISI 304 stainless steel

Probe Cable

1-metre length, 75 Ω triaxial,

fluoroethylene propylene (FEP)

insulated.

Probe

Connector

Gold-plated brass ClickLoc*

connector

Probe Tensile

Strength

330 N (75 lb) between probe cable

and case, maximum.

Housing

Material

Ultraviolet (UV) resistant, glassreinforced polyphenylene sulfide

(PPS) thermoplastic containing

conductive fibers.

Sleeve Material

and Retaining

Chain

AISI 304 stainless steel

Outer Sleeve

and Retaining

Screws

AISI 303 stainless steel

Sleeve O-Ring

Material

Neoprene

Grounding Liner

and Retaining

Plate Material

AISI 304 Stainless Steel

Vibration

Isolation

Material

Extra Soft Cellular Silicone

Lid Label

Material

Gloss Radiant White Polyester

Recommended

Torque

Retaining Nut

29.5 N·m (260 in·lb)

Probe Sleeve

Locknut

39.3 N·m (350 in·lb)

Housing

Strength Typical

Outer sleeve was mounted on a test stand with its axis parallel to horizontal and the housing mounted on the outer sleeve through an end hole. The housing supported 912 N (205 lbf) placed approximately 38 mm (1.5 in) from the unsupported end with the cover fastened in place and grounding liner installed.

Housing Impact

Strength

Certified by BASEEFA to withstand two separate 4 Joule (5.4 ft·lb) impacts at -39°C (-38°F) and at 115°C (239°F). CSA verified that samples of the housing and cover could withstand a 7 Joule (9.5 ft·lb) impact at ambient room temperature.

Total System

Weight

1.44 kg (3.2 lbm) typical with 0.3 metre (12 in) sleeve length.

Environmental Limits

Probe

Temperature

Range

Operating

Temperature:

-51 °C to +177 °C (-60 °F to +350 °F).

Note: Exposing the probe to temperatures below –34 °C (-29 °F) may cause premature failure of the pressure seal.

Power

Requires -17.5 Vdc to -26 Vdc without barriers at 12 mA maximum consumption, -23 Vdc to -26 Vdc with barriers. Operation at a more positive voltage than -23.5 Vdc can result in reduced linear range.

Supply
Sensitivity
Less than 2 mV change in output
voltage per volt change in input
voltage.
Output
resistance:
50 Ω
Field wiring:
0.2 to 1.5 mm2 (16 to 24 AWG) .
Recommend using 3-conductor
shielded triax cable and tinned
field wiring. Maximum length of
305 metres (1,000 feet) between
the 3300 XL Proximitor Sensor
and the monitor. See the
frequency response graph (Figure
1, page 7) for signal rolloff at high
frequencies when using longer
field wiring lengths.
Linear Range:
2 mm (80 mils). Linear range
begins at approximately 0.25 mm
(10 mils) from target and is from
0.25 mm to 2.3 mm (10 mils to 90
mils) (approximately –1 Vdc to –17
Vdc).
Recommended
Gap Setting:
1.27 mm (50 mils)
Incremental
Scale Factor
(ISF)
7.87 V/mm (200 mV/mil) ±5%
including interchangeability error
when measured in increments of
0.25 mm (10 mils) over the 80 mil
linear range from 0 °C to +45 °C
(+32 °F to +113 °F).
Deviation from best fit straight line (DSL)
Standard 1
metre system
Less than ±0.025mm (±1 mil) with
components at 0 °C to +45 °C
(+32 °F to +113 °F).
Frequency
Response
0 to 10 kHz: +0, -3 dB, with up to
305 metres (1000 feet) of field
wiring.
Minimum
Target Size
15.2 mm (0.6 in) diameter (flat
target)
Shaft Diameter
Minimum
50.8 mm (2.0 in)