Bently Nevada 330903&330904&330905&330910 Series Service Manual

330904-00-10-70-11-00

1. Description

Part Number:330904-00-10-70-11-00

3. Product Information

Part Number:330904-00-10-70-11-00

Model: 3300 NSv Proximity Probes

Manufacturer: Bently Nevada

Condition: New & Original in Factory Packing

Factory Warranty: 12 Months

Ordering Information

Model: 330904 - 3300 NSv Probe, M8X1 thread, with armor

Unthreaded Length Option: -00 - 00 mm

Overall Case Length Option: -10-100 mm

Total Length Option:70 7.0 meters (23.0 feet)

Connector and Cable Type Option:11 = Miniature coaxial ClickLoc connector with connector protector, FluidLoc cable

Agency Approval Option:00 Not required

Probe dc Resistance

Probe Length

(m) 7.0

Resistance from the Center

Conductor to the Outer

Conductor (RPROBE)

(ohms)

5.9 ± 0.9

The 3300 NSv probe and extension cable are mechanically and electrically compatible and interchangeable with Bently Nevada’s previous 3300 RAM proximity probe and extension cable. The NSv probe has increased chemical resistance compared to the 3300 RAM probe, which allows its use in many process compressor applications. The side-view characteristics of the 3300 NSv probe are also superior to those of the 3000-series 190 probe when gapping the 3300 NSv probe at the same distance from the probe target.

Extension cable

dc resistance

Center conductor: 0.220

Ω/m (0.067 Ω/ft)

Shield: 0.066 Ω/m (0.020

Ω/ft)

Extension cable

capacitance

69.9 pF/m (21.3 pF/ft)

typical

Field Wiring

0.2 to 1.5 mm2 (16 to 24

AWG)[0.25 to 0.75 mm2 (18

to 23 AWG) with ferrules].

Recommend using threeconductor shielded triad cable. Maximum length of 305 meters (1,000 feet) between the 3300 XL NSv Proximitor Sensor and the monitor. See the frequency response graphs Figure 16 and Figure 17 for signal rolloff at high frequencies when using longer field wiring lengths.

Linear Range

1.5 mm (60 mils). Linear

range begins at
approximately 0.25 mm (10
mils) from target and is
from 0.25 to 1.75 mm (10 to
70 mils) (approximately -1
to -13 Vdc).
Recommended
Gap Setting 1.0 mm (40 mils)
Incremental
Scale Factor
(ISF)
7.87 V/mm (200 mV/mil)
+12.5%/-20% including
interchangeability error
when measured in
increments of 0.25 mm (10
mils) over the 1.5 mm (60
mil) linear range.
Deviation from
best fit straight
line (DSL)
Less than ±0.06 mm (±2.3
mils).
Frequency
Response
0 to 10 kHz: +0, -3 dB
typical, with up to 305
meters (1000 feet) of field
wiring.
Target Size (flat
target)
Minimum: 8.9 mm (0.35 in)
diameter
Recommended minimum:
13 mm (0.5 in) diameter
Axial position
measurements on shaft
diameters smaller than 13
mm (0.5 in) will generally
result in a change in scale
factor. Reducing the gap
between the probe and
target will help limit the
change in scale factor. See
Figure 12 for additional
information.
Probe Tip
Material Polyphenylene sulfide (PPS).
Probe Case
Material AISI 304 stainless steel (SST).
Probe Cable
Specifications
75 Ω coaxial, fluoroethylene
propylene (FEP) insulated
probe cable in the following
total probe lengths: 0.5, 1, 5,
or 7 meters.
Recommended
torque Finger tight

Maximum torque 0.56 N•m (5 in•lb)

Minimum Bend Radius (with or without sst armor)

25.4 mm (1.0 in)

Operating Temperature

-52°C to +177°C (-62°F to +351°F)

Storage Temperature

-52°C to +177°C (-62°F to +351°F)

Probe Pressure

3300 NSv probes are designed to seal differential pressure between the probe tip and case. The probe sealing material consists of a Viton O-ring. Probes are not pressure tested prior to shipment. Contact our custom design department if you require a test of the pressure seal for your application.

Connector-to-connector Torque

Probe Case Torque

Maximum Rated Recommended

1/4-28 or M8X1 probe cases

7.3 N•m (65 in•lb)

5.1 N•m (45 in•lb)

Probe Case Thread

Maximum Length of Thread Engagement

M8x1 12 mm