GE RX3i PacSystem Series Service Manual

IC695CPE302

1. Description

The IC695CPE302 CPU is an RX3i Central Processing Unit made by GE Fanuc. It has 2 MB of storage space, 1.1 GHz of processor speed, 16k bits for thediscrete I/O, and 16k words for the analog I/O.

2. Specifications

Specification	Value
Brand	GE Fanuc
Series	RX3i PacSystem
Part	Number IC695CPE302
Product	Description RX3i CPU
Program	Storage 2 MB of User Memory
Type	of Memory Storage SRAM, Flash
Processor	Speed 1.1 GHz
Power	Requirements 1 Amp at +5 and +3.3 Volts DC, 0.5 Amps at +24 Volts DC
Serial	Communication RS-232
Ethernet	Port Yes
USB	Interface Standard 2.0
Protocol	Support Modbus RTU Slave, SNP Slave, Serial I/O
Backplane	Universal backplane
Number	of Status LEDs 8
Operating	Temperature 0 to 60 degree Celsius
Brand	GE Fanuc
Series	RX3i PacSystem
Part	Number IC695CPE302
Product	Description RX3i CPU
Program	Storage 2 MB of User Memory
Type	of Memory Storage SRAM, Flash
Processor	Speed 1.1 GHz
Power	Requirements 1 Amp at +5 and +3.3 Volts DC, 0.5 Amps at +24 Volts DC
Serial	Communication RS-232
Ethernet	Port Yes
USB	Interface Standard 2.0
Protocol	Support Modbus RTU Slave, SNP Slave, Serial I/O
Backplane	Universal backplane
Number	of Status LEDs 8
Operating	Temperature 0 to 60 degree Celsius

3. Product Information

The IC695CPE302 CPU is an RX3i Central Processing Unit made by GE Fanuc. It has 2 MB of storage space, 1.1 GHz of processor speed, 16k bits for thediscrete I/O, and 16k words for the analog I/O.

Technical specifications for IC695CPE302

Brand GE Fanuc

Series RX3i PacSystem

Part Number IC695CPE302

Product Description RX3i CPU

Program Storage 2 MB of User Memory

Type of Memory Storage SRAM, Flash

Processor Speed 1.1 GHz

Power Requirements 1 Amp at +5 and +3.3 Volts DC, 0.5 Amps at +24 Volts DC

Serial Communication RS-232

Ethernet Port Yes

USB Interface Standard 2.0

Protocol Support Modbus RTU Slave, SNP Slave, Serial I/O

Backplane Universal backplane

Number of Status LEDs 8

Operating Temperature 0 to 60 degree Celsius

Technical specifications for IC695CPE302

Brand GE Fanuc

Series RX3i PacSystem

Part Number IC695CPE302

Product Description RX3i CPU

Program Storage 2 MB of User Memory

Type of Memory Storage SRAM, Flash

Processor Speed 1.1 GHz

Power Requirements 1 Amp at +5 and +3.3 Volts DC, 0.5 Amps at +24 Volts DC

Serial Communication RS-232

Ethernet Port Yes

USB Interface Standard 2.0

Protocol Support Modbus RTU Slave, SNP Slave, Serial I/O

Backplane Universal backplane

Number of Status LEDs 8

Operating Temperature 0 to 60 degree Celsius