

Schneider Series Service Manual

ATV71H037M3

1. Description

The ATV71H037M3 variable speed drive from Schneider Electric is engineered for reliable control of three-phase motors. It operates within a voltage range of 200-240 V AC and has a power rating of 0.37 kW (0.5 hp).

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Line Altivar 71
Part	Number ATV71H037M3
EAN	3389118064201
Weight	2.06 lbs (0.94 kg)
Product	Variable Speed Drive
Power	Rating 0.37 kW
Number	of Phases 3
Voltage	200-240 V AC
Horsepower	Rating 0.5 hp
Max	Motor Cable Length 100 m
Line	Current 3.1A/3.5 A
EMC	Filter Integrated
Assembly	Style With Heat Sink
Apparent	Power 1.3 kVA
Prospective	Line Current 5 kA
Output	Frequency 0.1 to 599 Hz
Tightening	Torque 5.3 lbf.in
Insulation	Resistance > 1 mΩ at 500 V DC for 1 minute to earth
Communication	Port Protocol CANopen, Modbus

3. Product Information

The ATV71H037M3 variable speed drive from Schneider Electric is engineered for reliable control of three-phase motors. It operates within a voltage range of 200-240 V AC and has a power rating of 0.37 kW (0.5 hp).

Technical specifications for ATV71H037M3

Manufacturer Schneider Electric

Product Line Altivar 71

Part Number ATV71H037M3

EAN 3389118064201

Weight 2.06 lbs (0.94 kg)

Product Variable Speed Drive

Power Rating 0.37 kW

Number of Phases 3

Voltage 200-240 V AC

Horsepower Rating 0.5 hp

Max Motor Cable Length 100 m

Line Current 3.1A/3.5 A

EMC Filter Integrated

Assembly Style With Heat Sink

Apparent Power 1.3 kVA

Prospective Line Current 5 kA

Output Frequency 0.1 to 599 Hz

Tightening Torque 5.3 lbf.in

Insulation Resistance > 1 mΩ at 500 V DC for 1 minute to earth

Communication Port Protocol CANopen, Modbus

Description

The ATV71H037M3 model is a variable speed drive developed by Schneider Electric, purposefully designed for three-phase motor management. This drive functions effectively with a power rating of 0.37 kW, translating to a horsepower capacity of 0.5 hp. It operates at input voltages between 200 and 240 V AC, making it suitable for various industrial applications. The drive can withstand line currents of 3.1 A to 3.5 A, and its apparent power reaches 1.3 kVA. It is built with an integrated EMC filter, which plays a critical role in reducing electromagnetic interference, thus facilitating dependable operation in environments where electrical noise may be present.

A key feature is its capability to manage output frequencies from 0.1 Hz up to 599 Hz, providing a wide range of control for motor speeds. For installation flexibility, the maximum permissible length for the motor cable is 100 meters. The drive is constructed with a heat sink assembly style to help efficiently dissipate heat during operation, ensuring longevity and reliability.

In addition, the prospective line current stands at 5 kA, supporting robust performance during fault conditions. Tightening torque specifications are noted at 5.3 lbf.in, ensuring secure connections within the system. The insulation resistance exceeds 1 Megaohm when tested at 500 V DC for one minute, confirming solid safety against grounding issues. To enhance integration capabilities, the drive features communication ports that support CANopen and Modbus protocols, allowing for streamlined data exchange with other devices.

Range of Product

Altivar 71

Product or Component Type

Variable speed drive

Product Specific Application

Complex, high-power machines

Component name

ATV71

Motor power kW

0.37 kW, 3 phase 200...240 V

Maximum Horse Power Rating

0.5 hp, 3 phase 200...240 V

Maximum motor cable length

164.04 ft (50 m) shielded cable

328.08 ft (100 m) unshielded cable

power supply voltage

200...240 V - 15...10 %

Phase

3 phase

Line current

3.1 A 240 V 3 phase 0.37 kW / 0.5 hp

3.5 A 200 V 3 phase 0.37 kW / 0.5 hp

EMC filter

Integrated

Assembly style

With heat sink

Apparent power

1.3 kVA 240 V 3 phase 0.37 kW / 0.5 hp

Prospective line Isc

5 kA 3 phase

Nominal output current

3 A 4 kHz 230 V 3 phase 0.37 kW / 0.5 hp

Maximum transient current

4.5 A 60 s 3 phase 0.37 kW / 0.5 hp

4.9 A 2 s 3 phase 0.37 kW / 0.5 hp

Output frequency

0.1...599 Hz

Nominal switching frequency

4 kHz

Switching frequency

1...16 kHz adjustable

4...16 kHz with derating factor

Asynchronous motor control profile

ENA (Energy adaptation) system for unbalanced loads

Sensorless flux vector control (SFVC) (voltage or current vector)

Voltage/frequency ratio (2 or 5 points)

Flux vector control (FVC) with sensor (current vector)

Type of polarization

No impedance Modbus

Complementary

Product destination

Synchronous motors

Asynchronous motors

power supply voltage limits

170...264 V

power supply frequency

50...60 Hz - 5...5 %

power supply frequency limits

47.5...63 Hz

Speed range

1...100 asynchronous motor in open-loop mode, without speed feedback

1...1000 asynchronous motor in closed-loop mode with encoder feedback

1...50 synchronous motor in open-loop mode, without speed feedback

Speed accuracy

+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn

+/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn

Torque accuracy

+/- 15 % in open-loop mode, without speed feedback

+/- 5 % in closed-loop mode with encoder feedback

Transient overtorque

170 % +/- 10 % 60 s every 10 minutes

220 % +/- 10 % 2 s

Braking torque

<= 150 % with braking or hoist resistor

30 % without braking resistor

Synchronous motor control profile

Vector control without speed feedback

Regulation loop

Adjustable PI regulator

Motor slip compensation

Not available in voltage/frequency ratio (2 or 5 points)

Suppressable

Adjustable

Automatic whatever the load

diagnostic

1 LED (red) for drive voltage

Output voltage

<= power supply voltage

Insulation

Electrical between power and control

type of cable for mounting in an enclosure

With a NEMA Type1 kit 3 UL 508 cable 104 °F (40 °C), copper 75 °C / PVC

With an IP21 or an IP31 kit 3 IEC cable 104 °F (40 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 90 °C / XLPE/EPR

Electrical connection

Terminal 2.5 mm², AWG 14 AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

Terminal 4 mm², AWG 10 L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Tightening torque

5.3 lbf.in (0.6 N.m) AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

12.4 lbf.in (1.4 N.m), 12.3 lb.in L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Supply

Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection

Internal supply 24 V DC 21...27 V), <200 mA overload and short-circuit protection

Analogue input number

2

Analogue input type

AI1-/AI1+ bipolar differential voltage +/- 10 V DC 24 V max 11 bits + sign

AI2 software-configurable current 0...20 mA 242 Ohm 11 bits

AI2 software-configurable voltage 0...10 V DC 24 V max 30000 Ohm 11 bits

input sampling time

2 ms +/- 0.5 ms AI1-/AI1+) - analog

2 ms +/- 0.5 ms AI2) - analog

2 ms +/- 0.5 ms LI1...LI5) - discrete

2 ms +/- 0.5 ms LI6)if configured as logic input - discrete

Response time

<= 100 ms in STO (Safe Torque Off)

AO1 2 ms +/- 0.5 ms analog

R1A, R1B, R1C 7 ms +/- 0.5 ms discrete

R2A, R2B 7 ms +/- 0.5 ms discrete

absolute accuracy precision

+/- 0.6 % AI1-/AI1+) for a temperature variation 60 °C

+/- 0.6 % AI2) for a temperature variation 60 °C

+/- 1 % AO1) for a temperature variation 60 °C

Linearity error

+/- 0.15 % of maximum value AI1-/AI1+, AI2)

+/- 0.2 % AO1)

Analogue output number

1

Analogue output type

AO1 software-configurable logic output 10 V 20 mA

AO1 software-configurable current 0...20 mA 500 Ohm 10 bits

AO1 software-configurable voltage 0...10 V DC 470 Ohm 10 bits

Discrete output number

2

Discrete output type

Configurable relay logic R1A, R1B, R1C) NO/NC - 100000 cycles

Configurable relay logic R2A, R2B) NO - 100000 cycles

Minimum switching current

3 mA 24 V DC configurable relay logic

Maximum switching current

R1, R2 2 A 250 V AC inductive, cos phi = 0.4

R1, R2 2 A 30 V DC inductive, cos phi = 0.4

R1, R2 5 A 250 V AC resistive, $\cos \phi = 1$

R1, R2 5 A 30 V DC resistive, $\cos \phi = 1$

Discrete input number

7

Discrete input type

LI1...LI5 programmable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable PTC probe 0...6 1500 Ohm

PWR safety input 24 V DC 1500 Ohm ISO 13849-1 level d

Discrete input logic

Negative logic (sink) LI1...LI5), $> 16 \text{ V}$, $< 10 \text{ V}$

Positive logic (source) LI1...LI5), $< 5 \text{ V}$, $> 11 \text{ V}$

Negative logic (sink) LI6)if configured as logic input, $> 16 \text{ V}$, $< 10 \text{ V}$

Positive logic (source) LI6)if configured as logic input, $< 5 \text{ V}$, $> 11 \text{ V}$

Acceleration and deceleration ramps

S, U or customized

Linear adjustable separately from 0.01 to 9000 s

Automatic adaptation of ramp if braking capacity exceeded, by using resistor

Braking to standstill

By DC injection

Protection type

Against exceeding limit speed drive

Against input phase loss drive

Break on the control circuit drive

Input phase breaks drive

Line supply overvoltage drive

Line supply undervoltage drive

Overcurrent between output phases and earth drive

Overheating protection drive

Overvoltages on the DC bus drive

Short-circuit between motor phases drive

Thermal protection drive

Motor phase break motor

Power removal motor

Thermal protection motor

Insulation resistance

$> 1 \text{ mOhm}$ 500 V DC for 1 minute to earth

Frequency resolution

Analog input 0.024/50 Hz

Display unit 0.1 Hz

Communication Port Protocol

CANopen

Modbus

Connector type

1 RJ45 on front face)Modbus

1 RJ45 on terminal)Modbus

Male SUB-D 9 on RJ45CANopen

Physical interface

2-wire RS 485 Modbus

Transmission frame

RTU Modbus

Transmission rate

4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal

9600 bps, 19200 bps Modbus on front face

20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen

Data format

8 bits, 1 stop, even parity Modbus on front face

8 bits, odd even or no configurable parity Modbus on terminal

Number of addresses

1...127 CANopen
1...247 Modbus
Method of access
Slave CANopen
Marking
CE
Operating position
Vertical +/- 10 degree
Height
9.06 in (230 mm)
Depth
6.9 in (175 mm)
Width
5.1 in (130 mm)
Net Weight
6.6 lb(US) (3 kg)
Option card
Communication card CC-Link
Controller inside programmable card
Communication card DeviceNet
Communication card EtherNet/IP
Communication card Fipio
I/O extension card
Communication card Interbus-S
Interface card for encoder
Communication card Modbus Plus
Communication card Modbus TCP
Communication card Modbus/Uni-Telway
Overhead crane card
Communication card Profibus DP
Communication card Profibus DP V1
Environment
Noise level
43 dB 86/188/EEC
Dielectric strength
2830 V DC between earth and power terminals
4230 V DC between control and power terminals
Electromagnetic compatibility
1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5
Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6
Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4
Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2
Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3
Voltage dips and interruptions immunity test conforming to IEC 61000-4-11
Standards
EN 61800-3 environments 1 category C2
EN/IEC 61800-5-1
EN 55011 class A group 1
EN/IEC 61800-3
IEC 60721-3-3 class 3S2
EN 61800-3 environments 2 category C2
IEC 60721-3-3 class 3C1
UL Type 1
Product Certifications
GOST
UL
NOM 117
C-tick
CSA

Pollution degree

2 EN/IEC 61800-5-1

IP degree of protection

IP20 on upper part without blanking plate on cover EN/IEC 60529

IP20 on upper part without blanking plate on cover EN/IEC 61800-5-1

IP21 EN/IEC 60529

IP21 EN/IEC 61800-5-1

IP41 on upper part EN/IEC 60529

IP41 on upper part EN/IEC 61800-5-1

IP54 on lower part EN/IEC 60529

IP54 on lower part EN/IEC 61800-5-1

Vibration resistance

1 gn (f= 13...200 Hz) conforming to EN/IEC 60068-2-6

1.5 mm peak to peak (f= 3...13 Hz) conforming to EN/IEC 60068-2-6

Shock resistance

15 gn 11 ms EN/IEC 60068-2-27

Relative humidity

5...95 % without condensation IEC 60068-2-3

5...95 % without dripping water IEC 60068-2-3

Ambient air temperature for operation

14...122 °F (-10...50 °C) (without derating)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Operating altitude

<= 3280.84 ft (1000 m) without derating

3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m

Ordering and shipping details

Category

US1CP4C22130

Discount Schedule

CP4C

GTIN

3389118064201

Returnability

No

Packing Units

Unit Type of Package 1

PCE

Nbr. of units in pkg.

1

Package 1 Height

9.3 in (23.5 cm)

Package 1 Width

9.6 in (24.5 cm)

Package 1 Length

12.008 in (30.5 cm)

Package weight(Lbs)

9.218 lb(US) (4.181 kg)