

Schneider Series Service Manual

ATV71HC11N4D

1. Description

The ATV71HC11N4D is a variable speed drive from Schneider Electric's Altivar 71 series. Designed for three-phase applications, it operates within a rated voltage range of 380 to 480 V and offers significant power at 150 horsepower with a current rating of 163 A.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type Variable Speed Drive
Product	Line Altivar 71
Part	Number ATV71HC11N4D
Weight	268.00 lbs (121.56 kg)
Number	Of Phase 3-Phase
Rated	Voltage 380-480 V
Voltage	Type AC
Min.	Frequency Range 50 Hz
Max.	Frequency Range 60 Hz
Rated	Current 163 A
Rated	Power 150 Hp
Braking	to Standstill DC injection
Communication	Protocols CANopen and Modbus
I/O	Type Analog I/O
IP	Protection IP54
Mounting	Type Door Mount

3. Product Information

The ATV71HC11N4D is a variable speed drive from Schneider Electric's Altivar 71 series. Designed for three-phase applications, it operates within a rated voltage range of 380 to 480 V and offers significant power at 150 horsepower with a current rating of 163 A.

Technical specifications for ATV71HC11N4D

Manufacturer Schneider Electric

Product Type Variable Speed Drive

Product Line Altivar 71

Part Number ATV71HC11N4D

Weight 268.00 lbs (121.56 kg)

Number Of Phase 3-Phase

Rated Voltage 380-480 V

Voltage Type AC

Min. Frequency Range 50 Hz

Max. Frequency Range 60 Hz

Rated Current 163 A

Rated Power 150 Hp

Braking to Standstill DC injection

Communication Protocols CANopen and Modbus

I/O Type Analog I/O

IP Protection IP54

Mounting Type Door Mount

Description

Schneider Electric's ATV71HC11N4D is a robust variable speed drive designed to manage three-phase power systems. This drive operates efficiently within a rated voltage input of 380 to 480 volts AC. It can handle a rated current of 163 amperes while providing an output of 150 horsepower, making it suitable for a range of applications requiring variable speed control.

The ATV71HC11N4D operates within a frequency spectrum from 50 Hz to 60 Hz, providing flexible options for various motor specifications. To ensure effective stopping, this drive utilizes DC injection braking, offering enhanced control in halting operations. Furthermore, it is equipped with communication capabilities, supporting both CANopen and Modbus protocols, facilitating seamless integration into automation systems.

For connectivity and control, the drive features analog I/O options. Its enclosure holds an IP54 rating, ensuring suitable protection against dust and water exposure, which is essential for durability in industrial settings. This model is designed for door mounting, streamlining installation processes within control panels and similar setups. The ATV71HC11N4D exemplifies efficiency and reliability, making it an ideal choice for managing variable speed in demanding environments.

Range of Product

Altivar 71

Product or Component Type

Variable speed drive

Product Specific Application

Complex, high-power machines

Component name

ATV71

Motor power kW

110 kW, 3 phase 380...480 V

Maximum Horse Power Rating

150 hp, 3 phase 380...480 V

Maximum motor cable length

328.08 ft (100 m) shielded cable

656.2 ft (200 m) unshielded cable

power supply voltage

380...480 V - 15...10 %

Phase

3 phase

Line current

163 A 480 V 3 phase 110 kW / 150 hp

202 A 380 V 3 phase 110 kW / 150 hp

EMC filter

Integrated

Assembly style

With heat sink

Variant

Reinforced version

Without DC choke

Apparent power

133 kVA 380 V 3 phase 110 kW / 150 hp

Prospective line Isc

35 kA 3 phase

Nominal output current

215 A 2.5 kHz 380 V 3 phase 110 kW / 150 hp

215 A 2.5 kHz 460 V 3 phase 110 kW / 150 hp

Maximum transient current

323 A 60 s 3 phase 110 kW / 150 hp

355 A 2 s 3 phase 110 kW / 150 hp

Output frequency

0.1...500 Hz

Nominal switching frequency

2.5 kHz

Switching frequency

2.5...8 kHz adjustable

2.5...8 kHz with derating factor

Asynchronous motor control profile

Flux vector control (FVC) with sensor (current vector)

Voltage/frequency ratio (2 or 5 points)

Sensorless flux vector control (SFVC) (voltage or current vector)

ENA (Energy adaptation) system for unbalanced loads

Type of polarization

No impedance Modbus

Complementary

Product destination

Asynchronous motors

Synchronous motors

power supply voltage limits

323...528 V

power supply frequency

50...60 Hz - 5...5 %

power supply frequency limits

47.5...63 Hz

Speed range

1...100 asynchronous motor in open-loop mode, without speed feedback

1...1000 asynchronous motor in closed-loop mode with encoder feedback

1...50 synchronous motor in open-loop mode, without speed feedback

Speed accuracy

+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn

+/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn

Torque accuracy

+/- 15 % in open-loop mode, without speed feedback

+/- 5 % in closed-loop mode with encoder feedback

Transient overtorque

170 % +/- 10 % 60 s every 10 minutes

220 % +/- 10 % 2 s

Braking torque

<= 150 % with braking or hoist resistor

30 % without braking resistor

Synchronous motor control profile

Vector control without speed feedback

Regulation loop

Adjustable PI regulator

Motor slip compensation

Suppressable

Adjustable

Not available in voltage/frequency ratio (2 or 5 points)

Automatic whatever the load

diagnostic

1 LED (red) for drive voltage

Output voltage

<= power supply voltage

Insulation

Electrical between power and control

type of cable for mounting in an enclosure

With a NEMA Type1 kit 3 UL 508 cable 104 °F (40 °C), copper 75 °C / PVC

With an IP21 or an IP31 kit 3 IEC cable 104 °F (40 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 90 °C / XLPE/EPR

Electrical connection

Terminal 2.5 mm², AWG 14 AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

Terminal 2 x 100 mm² L1/R, L2/S, L3/T, U/T1, V/T2, W/T3)

Terminal 60 mm² PA, PB)

Terminal 2 x 150 mm² PC/-, PO, PA/+)

Tightening torque

5.3 lbf.in (0.6 N.m) AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

212.4 lbf.in (24 N.m), 212 lb.in L1/R, L2/S, L3/T, U/T1, V/T2, W/T3)

106.2 lbf.in (12 N.m), 106 lb.in PA, PB)

362.9 lbf.in (41 N.m), 360 lb.in PC/-, PO, PA/+)

Supply

Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection

Internal supply 24 V DC 21...27 V), <200 mA overload and short-circuit protection

Analogue input number

2

Analogue input type

AI1-/AI1+ bipolar differential voltage +/- 10 V DC 24 V max 11 bits + sign

AI2 software-configurable current 0...20 mA 242 Ohm 11 bits

AI2 software-configurable voltage 0...10 V DC 24 V max 30000 Ohm 11 bits

input sampling time

2 ms +/- 0.5 ms AI1-/AI1+) - analog

2 ms +/- 0.5 ms AI2) - analog

2 ms +/- 0.5 ms LI1...LI5) - discrete

2 ms +/- 0.5 ms LI6)if configured as logic input - discrete

Response time

<= 100 ms in STO (Safe Torque Off)

AO1 2 ms +/- 0.5 ms analog

R1A, R1B, R1C 7 ms +/- 0.5 ms discrete

R2A, R2B 7 ms +/- 0.5 ms discrete

absolute accuracy precision

+/- 0.6 % AI1-/AI1+) for a temperature variation 60 °C

+/- 0.6 % AI2) for a temperature variation 60 °C

+/- 1 % AO1) for a temperature variation 60 °C

Linearity error

+/- 0.15 % of maximum value AI1-/AI1+, AI2)

+/- 0.2 % AO1)

Analogue output number

1

Analogue output type

AO1 software-configurable logic output 10 V 20 mA

AO1 software-configurable current 0...20 mA 500 Ohm 10 bits

AO1 software-configurable voltage 0...10 V DC 470 Ohm 10 bits

Discrete output number

2

Discrete output type

Configurable relay logic R1A, R1B, R1C) NO/NC - 100000 cycles

Configurable relay logic R2A, R2B) NO - 100000 cycles

Minimum switching current

3 mA 24 V DC configurable relay logic

Maximum switching current

R1, R2 2 A 250 V AC inductive, $\cos \phi = 0.4$

R1, R2 2 A 30 V DC inductive, $\cos \phi = 0.4$

R1, R2 5 A 250 V AC resistive, $\cos \phi = 1$

R1, R2 5 A 30 V DC resistive, $\cos \phi = 1$

Discrete input number

7

Discrete input type

LI1...LI5 programmable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable PTC probe 0...6 1500 Ohm

PWR safety input 24 V DC 1500 Ohm ISO 13849-1 level d

Discrete input logic

Negative logic (sink) LI1...LI5), $> 16 \text{ V}$, $< 10 \text{ V}$

Positive logic (source) LI1...LI5), $< 5 \text{ V}$, $> 11 \text{ V}$

Negative logic (sink) LI6)if configured as logic input, $> 16 \text{ V}$, $< 10 \text{ V}$

Positive logic (source) LI6)if configured as logic input, $< 5 \text{ V}$, $> 11 \text{ V}$

Acceleration and deceleration ramps

Linear adjustable separately from 0.01 to 9000 s

S, U or customized

Automatic adaptation of ramp if braking capacity exceeded, by using resistor

Braking to standstill

By DC injection

Protection type

Against exceeding limit speed drive

Against input phase loss drive

Break on the control circuit drive

Input phase breaks drive

Line supply overvoltage drive

Line supply undervoltage drive

Overcurrent between output phases and earth drive

Overheating protection drive

Overvoltages on the DC bus drive

Short-circuit between motor phases drive

Thermal protection drive

Motor phase break motor

Power removal motor

Thermal protection motor

Insulation resistance

$> 1 \text{ mOhm}$ 500 V DC for 1 minute to earth

Frequency resolution

Analog input 0.024/50 Hz

Display unit 0.1 Hz

Communication Port Protocol

CANopen

Modbus

Connector type

1 RJ45 on front face)Modbus

1 RJ45 on terminal)Modbus

Male SUB-D 9 on RJ45CANopen

Physical interface

2-wire RS 485 Modbus

Transmission frame

RTU Modbus

Transmission rate

4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal

9600 bps, 19200 bps Modbus on front face

20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen

Data format

8 bits, 1 stop, even parity Modbus on front face

8 bits, odd even or no configurable parity Modbus on terminal

Number of addresses

1...127 CANopen

1...247 Modbus

Method of access

Slave CANopen

Marking

CE

Operating position

Vertical +/- 10 degree

Height

40.2 in (1022 mm)

Depth

14.8 in (377 mm)

Width

14.2 in (360 mm)

Net Weight

198.4 lb(US) (90 kg)

Option card

Communication card CC-Link

Controller inside programmable card

Communication card DeviceNet

Communication card EtherNet/IP

Communication card Fipio

I/O extension card

Communication card Interbus-S

Interface card for encoder

Communication card Modbus Plus

Communication card Modbus TCP

Communication card Modbus/Uni-Telway

Overhead crane card

Communication card Profibus DP

Communication card Profibus DP V1

Environment

Noise level

69.5 dB 86/188/EEC

Dielectric strength

3535 V DC between earth and power terminals

5092 V DC between control and power terminals

Electromagnetic compatibility

1.2/50 μ s - 8/20 μ s surge immunity test level 3 conforming to IEC 61000-4-5

Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6

Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4

Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2

Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3

Voltage dips and interruptions immunity test conforming to IEC 61000-4-11

Standards

EN 55011 class A group 2

EN 61800-3 environments 2 category C3

UL Type 1

EN/IEC 61800-5-1

EN/IEC 61800-3

IEC 60721-3-3 class 3C2

EN 61800-3 environments 1 category C3

Product Certifications

GOST

CSA

NOM 117

C-tick

UL

Pollution degree

2 EN/IEC 61800-5-1

3 UL 840

IP degree of protection

IP41 on upper part EN/IEC 60529

IP41 on upper part EN/IEC 61800-5-1

IP54 on lower part EN/IEC 60529

IP54 on lower part EN/IEC 61800-5-1

IP00 EN/IEC 60529

IP00 EN/IEC 61800-5-1

IP30 on side parts EN/IEC 60529

IP30 on side parts EN/IEC 61800-5-1

IP30 on the front panel EN/IEC 60529

IP30 on the front panel EN/IEC 61800-5-1

Vibration resistance

0.6 gn (f= 10...200 Hz) conforming to EN/IEC 60068-2-6

1.5 mm peak to peak (f= 3...10 Hz) conforming to EN/IEC 60068-2-6

Shock resistance

7 gn 11 ms EN/IEC 60068-2-27

Relative humidity

5...95 % without condensation IEC 60068-2-3

5...95 % without dripping water IEC 60068-2-3

Ambient air temperature for operation

14...122 °F (-10...50 °C) (without derating)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Operating altitude

<= 3280.84 ft (1000 m) without derating

3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m

Ordering and shipping details

Category

US1CP4C22133

Discount Schedule

CP4C

GTIN

3389119201162

Returnability

No