

Schneider Series Service Manual

ATV71HU30N4

1. Description

The ATV71HU30N4, manufactured by Schneider Electric, is a variable speed drive designed to deliver efficient motor control. It supports output currents ranging from 6.2 to 7.8 Amps and operates at a maximum output frequency of 599 Hz, making it versatile for various applications.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type Variable Speed Drive
Product	Line Altivar 71
Part	Number ATV71HU30N4
UPC	785901602866
Weight	11.00 lbs (4.99 kg)
Output	Current 6.2-7.8 A
Heat	Sink Yes
Output	Frequency 0.1-599 Hz
Operating	Temperature -10 to 50 °C
Motor	Power 3 kW (3 HP)
Frequency	50/60 Hz
IP	Protection IP20
Input	Voltage 380-480 VAC
Phase	3-phase
Input	Current 9-10.7 A (3 phase)
EMC	Filter Integrated
Output	Voltage 0-380/480 V (3 phase)
Assembly	Style With Heat Sink

3. Product Information

The ATV71HU30N4, manufactured by Schneider Electric, is a variable speed drive designed to deliver efficient motor control. It supports output currents ranging from 6.2 to 7.8 Amps and operates at a maximum output frequency of 599 Hz, making it versatile for various applications.

Technical specifications for ATV71HU30N4

Manufacturer Schneider Electric

Product Type Variable Speed Drive

Product Line Altivar 71

Part Number ATV71HU30N4

UPC 785901602866

Weight 11.00 lbs (4.99 kg)

Output Current 6.2-7.8 A

Heat Sink Yes

Output Frequency 0.1-599 Hz

Operating Temperature -10 to 50 °C

Motor Power 3 kW (3 HP)

Frequency 50/60 Hz

IP Protection IP20

Input Voltage 380-480 VAC

Phase 3-phase

Input Current 9-10.7 A (3 phase)

EMC Filter Integrated

Output Voltage 0-380/480 V (3 phase)

Assembly Style With Heat Sink

Description

The Schneider Electric ATV71HU30N4 is a reliable variable speed drive that excels in managing motor performance. This device operates with a current output between 6.2 and 7.8 Amps and is designed to handle a frequency range extending from 0.1 to 599 Hz. This allows for precise control over the connected motor's speed. Its power capacity is rated at 3 kW (3 HP), providing ample capability for various industrial applications.

In terms of connectivity, the ATV71HU30N4 is suitable for 3-phase input structures, operating within an input voltage range of 380 to 480 VAC. The drive has an input current rating of 9 to 10.7 Amps. An integrated electromagnetic compatibility (EMC) filter is included to reduce electrical noise and ensure compliance with standards. Furthermore, the drive outputs a voltage of 0 to 380/480 V, which is crucial for effective motor operation.

The assembly of this device incorporates a heat sink, enhancing its thermal management capabilities. The performance envelope extends across an operational temperature spectrum of -10 to +50 °C. The drive is also designed with an IP20 protection rating, signifying that it should be used in environments free of significant dust and moisture. Weighing 4.00 kg, the ATV71HU30N4 is both compact and effective, making it an ideal choice for applications requiring variable speed control.

Range of Product

Altivar 71

Product or Component Type

Variable speed drive

Product Specific Application

Complex, high-power machines

Component name

ATV71

Motor power kW

3 kW, 3 phase 380...480 V

Maximum motor cable length

164.04 ft (50 m) shielded cable

328.08 ft (100 m) unshielded cable

power supply voltage

380...480 V - 15...10 %

Phase

3 phase

Line current

9 A 480 V 3 phase 3 kW

10.7 A 380 V 3 phase 3 kW

EMC filter

Integrated

Assembly style

With heat sink

Apparent power

7 kVA 380 V 3 phase 3 kW

Prospective line Isc

5 kA 3 phase

Nominal output current

6.2 A 4 kHz 460 V 3 phase 3 kW

7.8 A 4 kHz 380 V 3 phase 3 kW

Maximum transient current

11.7 A 60 s 3 phase 3 kW

12.9 A 2 s 3 phase 3 kW

Output frequency

0.1...599 Hz

Nominal switching frequency

4 kHz

Switching frequency

1...16 kHz adjustable

4...16 kHz with derating factor

Asynchronous motor control profile

ENA (Energy adaptation) system for unbalanced loads

Voltage/frequency ratio (2 or 5 points)

Sensorless flux vector control (SFVC) (voltage or current vector)

Flux vector control (FVC) with sensor (current vector)

Type of polarization

No impedance Modbus

Complementary

Product destination

Synchronous motors

Asynchronous motors

power supply voltage limits

323...528 V

power supply frequency

50...60 Hz - 5...5 %

power supply frequency limits

47.5...63 Hz

Speed range

1...100 asynchronous motor in open-loop mode, without speed feedback

1...1000 asynchronous motor in closed-loop mode with encoder feedback

1...50 synchronous motor in open-loop mode, without speed feedback

Speed accuracy

+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn

+/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn

Torque accuracy

+/- 15 % in open-loop mode, without speed feedback

+/- 5 % in closed-loop mode with encoder feedback

Transient overtorque

170 % +/- 10 % 60 s every 10 minutes

220 % +/- 10 % 2 s

Braking torque

<= 150 % with braking or hoist resistor

30 % without braking resistor

Synchronous motor control profile

Vector control without speed feedback

Regulation loop

Adjustable PI regulator

Motor slip compensation

Not available in voltage/frequency ratio (2 or 5 points)

Suppressable

Automatic whatever the load

Adjustable

diagnostic

1 LED (red) for drive voltage

Output voltage

<= power supply voltage

Insulation

Electrical between power and control

type of cable for mounting in an enclosure

With a NEMA Type1 kit 3 UL 508 cable 104 °F (40 °C), copper 75 °C / PVC

With an IP21 or an IP31 kit 3 IEC cable 104 °F (40 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 90 °C / XLPE/EPR

Electrical connection

Terminal 2.5 mm², AWG 14 AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

Terminal 4 mm², AWG 10 L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Tightening torque

5.3 lbf.in (0.6 N.m) AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

12.4 lbf.in (1.4 N.m), 12.3 lb.in L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Supply

Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection

Internal supply 24 V DC 21...27 V), <200 mA overload and short-circuit protection

Analogue input number

2

Analogue input type

AI1-/AI1+ bipolar differential voltage +/- 10 V DC 24 V max 11 bits + sign

AI2 software-configurable current 0...20 mA 242 Ohm 11 bits

AI2 software-configurable voltage 0...10 V DC 24 V max 30000 Ohm 11 bits

input sampling time

2 ms +/- 0.5 ms AI1-/AI1+) - analog

2 ms +/- 0.5 ms AI2) - analog

2 ms +/- 0.5 ms LI1...LI5) - discrete

2 ms +/- 0.5 ms LI6)if configured as logic input - discrete

Response time

<= 100 ms in STO (Safe Torque Off)

AO1 2 ms +/- 0.5 ms analog

R1A, R1B, R1C 7 ms +/- 0.5 ms discrete

R2A, R2B 7 ms +/- 0.5 ms discrete

absolute accuracy precision

+/- 0.6 % AI1-/AI1+) for a temperature variation 60 °C

+/- 0.6 % AI2) for a temperature variation 60 °C

+/- 1 % AO1) for a temperature variation 60 °C

Linearity error

+/- 0.15 % of maximum value AI1-/AI1+, AI2)

+/- 0.2 % AO1)

Analogue output number

1

Analogue output type

AO1 software-configurable logic output 10 V 20 mA

AO1 software-configurable current 0...20 mA 500 Ohm 10 bits

AO1 software-configurable voltage 0...10 V DC 470 Ohm 10 bits

Discrete output number

2

Discrete output type

Configurable relay logic R1A, R1B, R1C) NO/NC - 100000 cycles

Configurable relay logic R2A, R2B) NO - 100000 cycles

Minimum switching current

3 mA 24 V DC configurable relay logic

Maximum switching current

R1, R2 2 A 250 V AC inductive, cos phi = 0.4

R1, R2 2 A 30 V DC inductive, cos phi = 0.4

R1, R2 5 A 250 V AC resistive, cos phi = 1

R1, R2 5 A 30 V DC resistive, cos phi = 1

Discrete input number

Discrete input type

LI1...LI5 programmable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable PTC probe 0...6 1500 Ohm

PWR safety input 24 V DC 1500 Ohm ISO 13849-1 level d

Discrete input logic

Negative logic (sink) LI1...LI5), > 16 V, < 10 V

Positive logic (source) LI1...LI5), < 5 V, > 11 V

Negative logic (sink) LI6)if configured as logic input, > 16 V, < 10 V

Positive logic (source) LI6)if configured as logic input, < 5 V, > 11 V

Acceleration and deceleration ramps

Automatic adaptation of ramp if braking capacity exceeded, by using resistor

Linear adjustable separately from 0.01 to 9000 s

S, U or customized

Braking to standstill

By DC injection

Protection type

Against exceeding limit speed drive

Against input phase loss drive

Break on the control circuit drive

Input phase breaks drive

Line supply overvoltage drive

Line supply undervoltage drive

Overcurrent between output phases and earth drive

Overheating protection drive

Overvoltages on the DC bus drive

Short-circuit between motor phases drive

Thermal protection drive

Motor phase break motor

Power removal motor

Thermal protection motor

Insulation resistance

> 1 mOhm 500 V DC for 1 minute to earth

Frequency resolution

Analog input 0.024/50 Hz

Display unit 0.1 Hz

Communication Port Protocol

Modbus

CANopen

Connector type

1 RJ45 on front face)Modbus

1 RJ45 on terminal)Modbus

Male SUB-D 9 on RJ45CANopen

Physical interface

2-wire RS 485 Modbus

Transmission frame

RTU Modbus

Transmission rate

4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal

9600 bps, 19200 bps Modbus on front face

20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen

Data format

8 bits, 1 stop, even parity Modbus on front face

8 bits, odd even or no configurable parity Modbus on terminal

Number of addresses

1...127 CANopen

1...247 Modbus

Method of access

Slave CANopen

Marking

CE

Operating position

Vertical +/- 10 degree

Height

10.2 in (260 mm)

Depth

7.4 in (187 mm)

Width

6.1 in (155 mm)

Net Weight

8.8 lb(US) (4 kg)

Functionality

Full

Specific application

Other applications

Option card

Communication card CC-Link

Controller inside programmable card

Communication card DeviceNet

Communication card EtherNet/IP

Communication card Fipio

I/O extension card

Communication card Interbus-S

Interface card for encoder

Communication card Modbus Plus

Communication card Modbus TCP

Communication card Modbus/Uni-Telway

Overhead crane card

Communication card Profibus DP

Communication card Profibus DP V1

Environment

Noise level

54.5 dB 86/188/EEC

Dielectric strength

3535 V DC between earth and power terminals

5092 V DC between control and power terminals

Electromagnetic compatibility

1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5

Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6

Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4

Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2

Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3

Voltage dips and interruptions immunity test conforming to IEC 61000-4-11

Standards

EN/IEC 61800-5-1

IEC 60721-3-3 class 3C1

EN 61800-3 environments 1 category C2

EN 61800-3 environments 2 category C2

UL Type 1

EN 55011 class A group 1

EN/IEC 61800-3

IEC 60721-3-3 class 3S2

Product Certifications

UL

GOST

NOM 117

CSA

C-tick

Pollution degree

2 EN/IEC 61800-5-1

IP degree of protection

IP20

Vibration resistance

1 gn (f= 13...200 Hz) conforming to EN/IEC 60068-2-6

1.5 mm peak to peak (f= 3...13 Hz) conforming to EN/IEC 60068-2-6

Shock resistance

15 gn 11 ms EN/IEC 60068-2-27

Relative humidity

5...95 % without condensation IEC 60068-2-3

5...95 % without dripping water IEC 60068-2-3

Ambient air temperature for operation

14...122 °F (-10...50 °C) (without derating)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Operating altitude

<= 3280.84 ft (1000 m) without derating

3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m

Ordering and shipping details

Category

US1CP4C22130

Discount Schedule

CP4C

GTIN

00785901602866

Returnability

No