

Schneider Series Service Manual

ATV71HU55N4Z

1. Description

The ATV71HU55N4Z is a variable speed drive produced by Schneider Electric, part of the Altivar 71 series. This model is capable of handling a motor power output of 5.5 kW, equivalent to 7.5 HP, operational within a voltage range of 380 to 480 V AC.

2. Specifications

Specification	Value
Manufacturer	Schneider Electric
Product	Type Variable Speed Drive
Product	Line Altivar 71
Part	Number ATV71HU55N4Z
EAN	3389118064720
Weight	12.00 lbs (5.44 kg)
Motor	Power Rating (kW) 5.5 kW
Motor	Power Rating (HP) 7.5 HP
Input	Voltage Range 380 to 480 V AC
Input	Phase 3-phase
Input	Frequency 50/60 Hz
Nominal	Input Current 14.3 A
Nominal	Output Current 11 A
Enclosure	Rating IP20
Control	Interface CANopen, Modbus
Operating	Temperature -10 to 50°C

3. Product Information

The ATV71HU55N4Z is a variable speed drive produced by Schneider Electric, part of the Altivar 71 series. This model is capable of handling a motor power output of 5.5 kW, equivalent to 7.5 HP, operational within a voltage range of 380 to 480 V AC.
Technical specifications for ATV71HU55N4Z
Manufacturer Schneider Electric
Product Type Variable Speed Drive
Product Line Altivar 71
Part Number ATV71HU55N4Z
EAN 3389118064720
Weight 12.00 lbs (5.44 kg)
Motor Power Rating (kW) 5.5 kW
Motor Power Rating (HP) 7.5 HP
Input Voltage Range 380 to 480 V AC
Input Phase 3-phase
Input Frequency 50/60 Hz
Nominal Input Current 14.3 A
Nominal Output Current 11 A
Enclosure Rating IP20
Control Interface CANopen, Modbus
Operating Temperature -10 to 50°C
Description
Schneider Electric's ATV71HU55N4Z denotes a variable speed drive within the Altivar 71 lineup. It operates at a voltage range of 380 to 480 volts AC, tailored for 3-phase applications. This drive boasts an impressive motor power rating of 5.5 kW, translating to approximately 7.5 horsepower, making it suitable for a variety of industrial motors. The operational characteristics include a nominal input current of 14.3 A and a nominal output current rated at 11 A. Designed to function at input frequencies of either 50 or 60 Hz, the ATV71HU55N4Z adapts to different electrical standards. The unit is housed in an enclosure rated IP20, indicating suitability for use in environments free from extreme dust and moisture. Operating temperature ranges from -10 to 50 degrees Celsius, allowing for versatile applications across different environmental conditions. The control capabilities are robust, featuring CANopen and Modbus interfaces for seamless communication with various systems. This drive has compact dimensions of 295 mm in height, 175 mm in width, and 187 mm in depth, while its weight is approximately 4.8 kg (10.58 lbs). The design considerations offer ease of integration into existing setups, ensuring that performance and reliability can be maintained across a wide range of operational tasks.
Range of Product
Altivar 71
Product or Component Type
Variable speed drive
Product Specific Application
Complex, high-power machines
Component name
ATV71
Motor power kW
5.5 kW, 3 phase 380...480 V
Maximum Horse Power Rating
7.5 hp, 3 phase 380...480 V
Maximum motor cable length
164.04 ft (50 m) shielded cable
328.08 ft (100 m) unshielded cable
power supply voltage
380...480 V - 15...10 %
Phase
3 phase
Line current
17 A 480 V 3 phase 5.5 kW / 7.5 hp
20.3 A 380 V 3 phase 5.5 kW / 7.5 hp
EMC filter
Integrated
Assembly style
With heat sink
Variant
Without remote graphic terminal
Apparent power
13.4 kVA 380 V 3 phase 5.5 kW / 7.5 hp

Prospective line Isc

22 kA 3 phase

Nominal output current

11 A 4 kHz 460 V 3 phase 5.5 kW / 7.5 hp

14.3 A 4 kHz 380 V 3 phase 5.5 kW / 7.5 hp

Maximum transient current

21.5 A 60 s 3 phase 5.5 kW / 7.5 hp

23.6 A 2 s 3 phase 5.5 kW / 7.5 hp

Output frequency

0.1...599 Hz

Nominal switching frequency

4 kHz

Switching frequency

1...16 kHz adjustable

4...16 kHz with derating factor

Asynchronous motor control profile

Voltage/frequency ratio (2 or 5 points)

ENA (Energy adaptation) system for unbalanced loads

Flux vector control (FVC) with sensor (current vector)

Sensorless flux vector control (SFVC) (voltage or current vector)

Type of polarization

No impedance Modbus

Complementary

Product destination

Synchronous motors

Asynchronous motors

power supply voltage limits

323...528 V

power supply frequency

50...60 Hz - 5...5 %

power supply frequency limits

47.5...63 Hz

Speed range

1...100 asynchronous motor in open-loop mode, without speed feedback

1...1000 asynchronous motor in closed-loop mode with encoder feedback

1...50 synchronous motor in open-loop mode, without speed feedback

Speed accuracy

+/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn

+/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn

Torque accuracy

+/- 15 % in open-loop mode, without speed feedback

+/- 5 % in closed-loop mode with encoder feedback

Transient overtorque

170 % +/- 10 % 60 s every 10 minutes

220 % +/- 10 % 2 s

Braking torque

<= 150 % with braking or hoist resistor

30 % without braking resistor

Synchronous motor control profile

Vector control without speed feedback

Regulation loop

Adjustable PI regulator

Motor slip compensation

Suppressable

Adjustable

Not available in voltage/frequency ratio (2 or 5 points)

Automatic whatever the load

diagnostic

1 LED (red) for drive voltage

Output voltage

$\leq$ power supply voltage

Insulation

Electrical between power and control

type of cable for mounting in an enclosure

With a NEMA Type1 kit 3 UL 508 cable 104 °F (40 °C), copper 75 °C / PVC

With an IP21 or an IP31 kit 3 IEC cable 104 °F (40 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 70 °C / PVC

Without mounting kit 1 IEC cable 113 °F (45 °C), copper 90 °C / XLPE/EPR

Electrical connection

Terminal 2.5 mm², AWG 14 AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

Terminal 6 mm², AWG 8 L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Tightening torque

5.3 lbf.in (0.6 N.m) AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)

26.6 lbf.in (3 N.m), 26.5 lb.in L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)

Supply

Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC $\pm$ 5 %, <10 mA overload and short-circuit protection

Internal supply 24 V DC 21...27 V), <200 mA overload and short-circuit protection

Analogue input number

2

Analogue input type

AI1-/AI1+ bipolar differential voltage $\pm$ 10 V DC 24 V max 11 bits + sign

AI2 software-configurable current 0...20 mA 242 Ohm 11 bits

AI2 software-configurable voltage 0...10 V DC 24 V max 30000 Ohm 11 bits

input sampling time

2 ms $\pm$ 0.5 ms AI1-/AI1+) - analog

2 ms $\pm$ 0.5 ms AI2) - analog

2 ms $\pm$ 0.5 ms LI1...LI5) - discrete

2 ms $\pm$ 0.5 ms LI6)if configured as logic input - discrete

Response time

$\leq$ 100 ms in STO (Safe Torque Off)

AO1 2 ms $\pm$ 0.5 ms analog

R1A, R1B, R1C 7 ms $\pm$ 0.5 ms discrete

R2A, R2B 7 ms $\pm$ 0.5 ms discrete

absolute accuracy precision

$\pm$ 0.6 % AI1-/AI1+) for a temperature variation 60 °C

$\pm$ 0.6 % AI2) for a temperature variation 60 °C

$\pm$ 1 % AO1) for a temperature variation 60 °C

Linearity error

$\pm$ 0.15 % of maximum value AI1-/AI1+, AI2)

$\pm$ 0.2 % AO1)

Analogue output number

1

Analogue output type

AO1 software-configurable logic output 10 V 20 mA

AO1 software-configurable current 0...20 mA 500 Ohm 10 bits

AO1 software-configurable voltage 0...10 V DC 470 Ohm 10 bits

Discrete output number

2

Discrete output type

Configurable relay logic R1A, R1B, R1C) NO/NC - 100000 cycles

Configurable relay logic R2A, R2B) NO - 100000 cycles

Minimum switching current

3 mA 24 V DC configurable relay logic

Maximum switching current

R1, R2 2 A 250 V AC inductive, $\cos \phi = 0.4$

R1, R2 2 A 30 V DC inductive, $\cos \phi = 0.4$

R1, R2 5 A 250 V AC resistive, $\cos \phi = 1$

R1, R2 5 A 30 V DC resistive, $\cos \phi = 1$

Discrete input number

7

Discrete input type

LI1...LI5 programmable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable 24 V DC level 1 PLC 3500 Ohm

LI6 switch-configurable PTC probe 0...6 1500 Ohm

PWR safety input 24 V DC 1500 Ohm ISO 13849-1 level d

Discrete input logic

Negative logic (sink) LI1...LI5), > 16 V, < 10 V

Positive logic (source) LI1...LI5), < 5 V, > 11 V

Negative logic (sink) LI6)if configured as logic input, > 16 V, < 10 V

Positive logic (source) LI6)if configured as logic input, < 5 V, > 11 V

Acceleration and deceleration ramps

Automatic adaptation of ramp if braking capacity exceeded, by using resistor

S, U or customized

Linear adjustable separately from 0.01 to 9000 s

Braking to standstill

By DC injection

Protection type

Against exceeding limit speed drive

Against input phase loss drive

Break on the control circuit drive

Input phase breaks drive

Line supply overvoltage drive

Line supply undervoltage drive

Overcurrent between output phases and earth drive

Overheating protection drive

Overvoltages on the DC bus drive

Short-circuit between motor phases drive

Thermal protection drive

Motor phase break motor

Power removal motor

Thermal protection motor

Insulation resistance

> 1 mOhm 500 V DC for 1 minute to earth

Frequency resolution

Analog input 0.024/50 Hz

Display unit 0.1 Hz

Communication Port Protocol

Modbus

CANopen

Connector type

1 RJ45 on front face)Modbus

1 RJ45 on terminal)Modbus

Male SUB-D 9 on RJ45CANopen

Physical interface

2-wire RS 485 Modbus

Transmission frame

RTU Modbus

Transmission rate

4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal

9600 bps, 19200 bps Modbus on front face

20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen

Data format

8 bits, 1 stop, even parity Modbus on front face

8 bits, odd even or no configurable parity Modbus on terminal

Number of addresses

1...127 CANopen

1...247 Modbus

Method of access

Slave CANopen

Marking

CE

Operating position

Vertical +/- 10 degree

Height

11.6 in (295 mm)

Depth

7.4 in (187 mm)

Width

6.9 in (175 mm)

Net Weight

12.1 lb(US) (5.5 kg)

Option card

Communication card CC-Link

Controller inside programmable card

Communication card DeviceNet

Communication card EtherNet/IP

Communication card Fipio

I/O extension card

Communication card Interbus-S

Interface card for encoder

Communication card Modbus Plus

Communication card Modbus TCP

Communication card Modbus/Uni-Telway

Overhead crane card

Communication card Profibus DP

Communication card Profibus DP V1

Environment

Noise level

55.6 dB 86/188/EEC

Dielectric strength

3535 V DC between earth and power terminals

5092 V DC between control and power terminals

Electromagnetic compatibility

1.2/50 µs - 8/20 µs surge immunity test level 3 conforming to IEC 61000-4-5

Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6

Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4

Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2

Radiated radio-frequency electromagnetic field immunity test level 3 conforming to IEC 61000-4-3

Voltage dips and interruptions immunity test conforming to IEC 61000-4-11

Standards

IEC 61800-3 environments 2 category C3

EN 55011 class A group 2

UL Type 1

IEC 61800-3 environments 1 category C3

IEC 60721-3-3 class 3S2

IEC 61800-3

IEC 61800-5-1

IEC 60721-3-3 class 3C1

Product Certifications

GOST

CSA

UL

NOM 117

C-tick

Pollution degree

2 IEC 61800-5-1

IP degree of protection

IP20 on upper part without blanking plate on cover IEC 60529

IP20 on upper part without blanking plate on cover IEC 61800-5-1

IP21 IEC 60529

IP21 IEC 61800-5-1

IP41 on upper part IEC 60529

IP41 on upper part IEC 61800-5-1

IP54 on lower part IEC 60529

IP54 on lower part IEC 61800-5-1

Vibration resistance

1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6

1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6

Shock resistance

15 gn 11 ms IEC 60068-2-27

Relative humidity

5...95 % without condensation IEC 60068-2-3

5...95 % without dripping water IEC 60068-2-3

Ambient air temperature for operation

14...122 °F (-10...50 °C) (without derating)

Ambient Air Temperature for Storage

-13...158 °F (-25...70 °C)

Operating altitude

<= 3280.84 ft (1000 m) without derating

3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m

Ordering and shipping details

Category

US1CP4C22131

Discount Schedule

CP4C

GTIN

3389118064720

Returnability

No